

SPECIFICATIONS

Model	RFP2408	RFP2808	RFP2410	RFP2810	RFP2412	RFP2812	RFP2415	RFP2815	RFP2418	RFP2818
Nominal Impedance	4	8	4	8	4	8	4	8	4	8
FS (Hz)	35	37	30	32	28	30	23	25	22	24
RE (Ohm)	3.7	7.3	3.7	7.3	3.7	7.3	3.7	7.3	3.9	7.8
LE (mH)	3.3	5.2	3.3	5.2	3.3	5.2	3.3	5.2	3.8	6.7
QMS	6.18	6.63	5.38	5.23	6.20	5.91	5.51	5.50	5.25	5.70
QES	0.39	0.50	0.39	0.47	0.52	0.71	0.42	0.55	0.49	0.575
QTS	0.37	0.47	0.36	0.43	0.48	0.64	0.39	0.50	0.46	0.522
VAS (cu.ft.)	0.635	0.635	1.62	1.62	4.23	4.23	11.86	11.86	14.44	14.44
VAS (liter)	18	18	46	46	120	120	336	336	409	409
Power (Watts RMS)	200	200	200	200	200	200	200	200	250	250
Power (Watts Peak)	400	400	400	400	400	400	400	400	500	500
SPL (dB @ 1w/1m)	85	85	87	87	89	89	92	92	92	92
X-MAX (inches)	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.31	0.39	0.39
X-MAX (mm)	8	8	8	8	8	8	8	8	10	10
Sealed Box Vol. (cu. ft.)	0.3	0.3	0.75	0.75	1.25	1.25	2.5	2.5	4.0	4.0
Ported Box Vol. (cu. ft.)	0.625	0.625	1.0	1.0	2.0	2.0	2.5	2.5	4.0	4.0
Speaker Dis. (cu. ft.)	0.05	0.05	0.06	0.06	0.09	0.09	0.113	0.113	0.19	0.19
Mounting Dia. (in.)	7 ¹ / ₁₆	7 ¹ / ₁₆	9 ⁵ / ₃₂	9 ⁵ / ₃₂	11	11	14	14	16 ¹⁹ / ₃₂	16 ¹⁹ / ₃₂
Mounting Depth (in.)	3 ¹³ / ₁₆	3 ¹³ / ₁₆	4 ¹ / ₂	4 ¹ / ₂	5 ³ / ₈	5 ³ / ₈	7 ¹ / ₈	7 ¹ / ₈	8 ¹ / ₂	8 ¹ / ₂

